
COMPLEMENTARY ROPE CONSTRUCTIONS


PYTHON 7 R+F

7 R+F is PYTHON's specifically designed premium quality carrying rope for skyline yarders. The increased contact surface provides much smoother carriage performance and increased braking grip.



PYTHON SOLID 8 C

Premium eight strand rope for increased breakload requirements and service life over six strand constructions. Its HiPac compaction and a very tight rope geometry makes it the ideal winch rope and boom hoist line for multi layer winches.



Nominal	Mass	Minimum breaking load	
diameter [mm/inch]	weight [kg/100m]	1960 N/mm ² [kN]	
16	124,0	259	
18	160,0	331	
20	195,0	404	
22	236,0	507	

Nominal		Mass .	Minimum breaking load		
	diameter weigl	weight [kg/100m]	1960 N/mm ² [kN]	2160 N/mm ² [kN]	
	1"	293,0	525	579	
	26	310,0	555	612	
	27	333,0	597	658	
	28	364,0	652	719	
	1-1/8"	375,0	673	742	
	29	385,3	691	762	
	30	411,4	738	814	
	31	445,6	799	881	
	1-1/4"	467,0	838	924	
	32	470,8	845	931	
	33	500,8	899	990	
	34	528,7	949	1.045	
	1-3/8"	564,0	1.012	1.115	
	35	564,9	1.014	1.117	
	36	595,0	1.068	1.176	
	38	670,0	1.202	1.324	
	1-1/2"	672,0	1.205	1.327	
	40	736,0	1.321	1.456	
	1-5/8"	783,0	1.405	1.548	
	42	814,0	1.461	1.610	
	44	892,0	1.600	1.764	
	1-3/4"	910,0	1.633	1.800	
	46	969,0	1.737	1.914	